



Part Numbers:

EU04066-02-FG (MSTS UD)
EU04232-01-FG (MSTS UDL)
EU03755-02-FG (MSTS UL)
EU04618-01-FG (MSTS UI3L)
EU04651-01-FG (MSTS UI3DL)

MULTI-SPECTRAL TEST SET (MSTS™)

GO/NO-GO TESTING

Following more than 25 years of individual flight-line test equipment designs (> 2,000 test sets in 19 different countries), Textron Systems Electronic Systems (TSES) now offers a combined test set that provides an integrated solution for all flight line stimulation requirements. The user definable MSTS provides multiple threat and detection channels to enable comprehensive testing of modern multi sensor electro-optic/infrared (EO/IR) aircraft survivability equipment (ASE) designs. Threats may be individual, sequential or staggered to offer realistic test requirements. The MSTS offers the user a choice of UV, 2 colour IR, Laser (LBR, LTD, LRF) and IR detection to cover the complete gamut of today's EO/IR and DIRCM threat environment.

By integrating the highly effective threat emitters into a compact and easily portable design, it offers a single cost-effective solution for post maintenance, pre-mission and development requirements. To complement the MSTS, TSES offers a newly designed software suite, Test Program Generator (TPG), to allow a user full threat development, loading, remote control and firing capabilities.

TEXTRON Systems

Electronic Systems


124 Industry Lane, Hunt Valley, MD 21030 | 800.655.2616 | electronicsystems@textronsystems.com
www.textronsystems.com/es

MULTI-SPECTRAL TEST SET (MSTS)

SYSTEM PERFORMANCE



Typical Operating Range
5 m - 100 m (configuration dependant)
5 m - 30 m (typical)



Memory Media Type
Removable Memory Media



Battery Life
> 200 engagement operations



Enhanced GUI User Interface
Sunlight readable LCD display



Aiming
Optical sight with optional IR sight



Weight (including battery)
< 4 kg/9 lb



Standard Color
NATO green



External Connection
Serial port providing ethernet and remote trigger



Dimensions (excluding handle)
225 (W) x 190 (H) x 300 (L) mm



Maximum Profile Length
32 sec



Power
Removable lithium rechargeable battery
12 VDC external input



Mounting Configuration
Handheld or monopod/tripod (not supplied)



Number of Test Profile Libraries
> 100

Laboratory, Depot and Flight-line Testing:

- Combined EO/IR Emitters/Detection
- Simultaneous, individual, or sequential ASE test emissions
- Upgradable functions from baseline purchase
- End-to-end DIRCM confidence test
 - Jam code & irradiance
- UV and IR Missile Warning System test
 - Hostile fire muzzle flash and missile plume
- Laser Warning Receiver test
 - 0.905 and 1.54 microns
 - Laser Range Finder, Laser Designator and Laser Beam Rider
- IR Jammer

Textron Systems Electronic Systems
124 Industry Lane
Hunt Valley, MD 21030
1-800-655-2616 or 410-666-1400
electronicsystems@textronsystems.com

Textron Systems Electronic Systems UK
16 Compass Point, Ensign Way
Hamble, Southampton Hampshire SO31 4RA
+(44) 2380455110
electronicsystems@textronsystems.com

TEXTRON Systems