

# THERMITE™ RS1



## UNSURPASSED MOBILITY WITH MAXIMUM STANDOFF

Thermite RS1 is the most capable, durable and reliable firefighting robot on the market. The RS1 is remotely operated with a backpack controller that provides high-definition and infrared video in real-time, allowing the machine to traverse hazardous terrain with maximum control. Manufactured by leaders in robotic innovation, RS1 has the power to push vehicles from its path, the agility to climb stairs and the ability to output a maximum 1,250 gpm at 200 psi. Fabricated using durable construction-grade components, the RS1 can navigate challenging terrains and withstand exposure to extreme elements. Thermite is designed as an advanced tool to help operators combat fires safely and efficiently.

+1 207.247.2777  
firesales@howeandhowe.com

**TEXTRON** Systems

 **HOWE & HOWE**

# THERMITE RS1



## SYSTEM

**TRACKS DESCRIPTION**  
Industrial-grade belted rubber

**POWER TRANSMISSION**  
Hydrostatic

**TYPE**  
Independent propulsion

**WINCH**  
5,000 lbs capacity

**VIDEO SYSTEM**  
DTV (standard)  
FLIR thermal (optional)



## MONITOR

**MAKE & MODEL**  
Elkhart Brass Cobra

**MAX STREAM HORIZONTAL**  
+300 ft / 100 m

**MAX STREAM VERTICAL**  
+150 ft / 50 m

**MAX PSI/BARS**  
200 psi

**FLOW**  
1,250 gpm



## DIMENSIONS

**VEHICLE WEIGHT**  
+/- 1,600 lb

**GROUND CLEARANCE**  
8 in

**LENGTH**  
77.25 in

**WIDTH**  
44 in

**HEIGHT**  
64 in



## SYSTEM PERFORMANCE

**MAX GRADE SLOPE**  
+50%

**MAX SIDE SLOPE**  
35%

**RANGE**  
300-500 environment dependent

**SPEED**  
6 mph



## ENGINE

**MAKE & MODEL**  
Kohler KDW1003

**ENGINE DESCRIPTION**  
24 hp, diesel, 4 stroke,  
water cooled



## FEATURES

- 24 hp diesel engine
- 1,250 gpm nozzle
- Stand off range of over 300-500 m
- Track and vehicle cooling sprayers
- Up to 20 hrs of runtime without refueling
- High strength construction grade tracks and road wheels
- Provides reconnaissance and situational awareness in high risk areas
- Optional attachments: foam nozzle and scene lighting